



#	QTY.	MATERIAL	DESCRIPTION
1	4	CSA HA5 6061-T6	76x76x6.4mm ANGLE FRAME
2	4	BLACK NEOPRENE	3mm x 76mm NEOPRENE GASKET
3	16	STAINLESS STEEL 304	1/4 X 3 1/4 WEDGE ANCHOR C/W NUT, FLAT AND LOCK WASHER
4	1	CSA HA5 6061-T6	6.4mm THK. TREAD PLATE
5	4	CSA HA5 6061-T6	25x6.4mm FLAT BAR STIFFENER
6	2	CSA HA5 6061-T6	9.5mm THK. PLATE (HINGE)
7	2	CSA HA5 6061-T6	38mmØ SOLID ROD (HINGE)
8	2	STAINLESS STEEL 316	5/8 X 3 1/2 HEX BOLT C/W FW & NYLON INSERT LOCK NUTS (HINGE)
9	2	CSA HA5 6061-T6	6 X 38MM FLAT BAR LOCK TAB C/W 12mmØ HOLE
10	1	STAINLESS STEEL 316	90° HOLD OPEN ARM
11	1	CSA HA5 6061-T6	12mmØ WELDED HANDLE

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND OTHER RIGHTS WHICH ARE THE SOLE AND EXCLUSIVE PROPERTY OF MSU MISSISSAUGA LTD.

POSSESSION OF THIS MATERIAL DOES NOT CONVEY OR TRANSFER ANY RIGHTS THEREIN, AND REPRODUCTION, USE, COPYING OR DISCLOSURE TO OTHERS IS FORBIDDEN WITHOUT THE PRIOR WRITTEN CONSENT OF AN OFFICER OF MSU MISSISSAUGA LTD.

© MSU MISSISSAUGA LTD. - JULY 23RD, 2014

NOTE: 1) ALL ALUMINUM SURFACES IN CONTACT WITH CONCRETE SHALL RECEIVE 2 COATS OF BITUMINOUS PAINT.  
 2) WELDING SHALL CONFORM TO CSA W47.2 CSA W59.2  
 3) GROUND ROUGH EDGES SMOOTH. WELDED SURFACES REMAIN AS WELDED.  
 3) REINFORCED TO WITHSTAND A LIVE LOAD OF 100 LBS/SQ.FT (4.8KPa) WITH MAX. 75 POUNDS

PROJECT	LOCATION PROJECT
CONTRACTOR	CONTRACTOR
ARCHT/ENGR	ENGINEER
QTY. 1	PROJECT NO. #

TITLE						MSU BD4 BOLT-DOWN ACCESS HATCH	
						900 x 900 CLEAR OPENING	
NO.	DATE	BY	DATE	NO.	DATE	BY	DATE
1				1			
SCALE NTS				DWD. NO. BD-1		PL. NO. CATA	