



#	QTY.	MATERIAL	DESCRIPTION
1	1	ALUMINUM 6351-T6	FRAME EXTRUSION #P5709-1 C/W 1/8 X 4" NEOPRENE SEAL GASKET
2	1	ALUMINUM 6061-T6	1/4" TREAD PLATE
3	6	ALUMINUM 6061-T6	1/4" X 3" FLAT BAR REINFORCING
4	1	BLACK CORD NEOPRENE	PERIMETER SEALING GASKET
5	12	ALUMINUM 6061-T6	1/2 X 3 3/4" WEDGE ANCHORS
6	3	STAINLESS STEEL 316	SS316 BUTT HINGES C/W 1/4" TAMPERPROOF FASTENERS
7	1	STAINLESS STEEL 316	GAS SPRING ASSIST CYLINDER C/W ALUM. MOUNTING BRACKETS
8	1	STAINLESS STEEL 316	90 DEG. HOLD OPEN ARM C/W 1/4"Ø ROD FORMED HANDLE
9	1	STAINLESS STEEL 316	SLAM LOCK C/W ALUM. REMOVABLE SEALING PLUG AND OPENING TOOL
10	1	ALUMINUM 6061-T6	FLUSH LIFT HANDLE
11	1	ALUMINUM 6061-T6	LOCK TAB (FOR EXTERNAL PAD LOCK)

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND OTHER RIGHTS WHICH ARE THE SOLE AND EXCLUSIVE PROPERTY OF MSU MISSISSAUGA LTD.

POSSESSION OF THIS MATERIAL DOES NOT CONVEY OR TRANSFER ANY RIGHTS THEREIN, AND REPRODUCTION, USE, COPYING OR DISCLOSURE TO OTHERS IS FORBIDDEN WITHOUT THE PRIOR WRITTEN CONSENT OF AN OFFICER OF MSU MISSISSAUGA LTD.

© MSU MISSISSAUGA LTD. - JULY 23RD, 2014

NOTE: 1) ALL ALUMINUM SURFACES IN CONTACT WITH CONCRETE SHALL RECEIVE 2 COATS OF BITUMINOUS PAINT.
 2) WELDING SHALL CONFORM TO CSA W47.2-R2008 CSA W59.2-R2008
 3) REINFORCED TO WITHSTAND A LIVE LOAD OF 300 LBS/SQ.FT (14.4KPa) WITH MAX. DEFLECTION OF 1/150th OF THE SPAN.

PROJECT	LOCATION
CONTRACTOR	PROJECT
ARCHT/ENGR	CONTRACTOR
QTY.	ENGINEER
1	PROJECT NO. #

TITLE		ALUMINUM ACCESS HATCH	
MSU TYPE-M BOLT DOWN C/W ASSIST		PL.NO. CATA	
NO.	DATE	BY	DATE
1		SCJ	##/##/##
REVISION	SCALE	CHK'D BY	DWG. NO.
	NTS		BD-2